



MTP810 Ex

ATEX TETRA Terminal

High performing communication and user safety



Part of Motorola's market leading range of ATEX TETRA terminals, the MTP810 Ex provides high quality communication with comprehensive user safety when in environments containing potentially explosive atmospheres.

Motorola is a world leader in the development and deployment of TETRA communication solutions, and the MTP810 Ex ATEX TETRA radio delivers safe and reliable communications for users with a powerful set of features to harness the capability of TETRA.

Key Features

High Performing Communication

- Strong rugged design for optimum reliability in harsh conditions
- Powerful, high quality audio in most demanding environments
- Full range of supporting ATEX certified accessories for a customised solution

Comprehensive User Safety

- ATEX & IEC-Ex gas and dust approvals
- Integrated GPS for user location
- Internal "Man Down" alarm

High Performance Communication

The MTP810 Ex delivers best in class audio performance in the typical noisy environments where specialist users from industry or public safety operate.

Comprehensive User Safety

The MTP810Ex can be used in explosive environments as per its ATEX certificate (i.e., indicated levels of protection). Operational safety is further enhanced with a range of features including:

- State of the art integrated GPS receiver providing the ability to locate personnel through the radio, improving user safety and resource management.
- Internal "Man Down" alert - this fully integrated solution triggers an emergency procedure when the carrier of the radio remains motionless for a set period or falls down.

Simple but Powerful User Interface

The simplified keypad with large button surface makes the MTP810 Ex easy to use with gloves. Combined with the large scalable display fonts and icons, the MTP810 Ex facilitates operation in difficult environments with limited visibility.

Data Applications Capability

The integrated WAP browser and Multi-Slot packet data enables rapid access to critical information in the field. Applications are further enhanced with the ability to have simultaneous Short Data Service (SDS) and Multi-Slot packet data services via the TNP1 protocol.

MTP810 Ex

ATEX TETRA HAND PORTABLE

ATEX SPECIFICATIONS

ATEX Rating	Gas	II 2G Ex ib IIA T3
	Dust	II 3D Ex ibD 22 IP6x T90°C
IEC EX Rating	Gas	Ex ib IIA T3 (Approved for Zone 1 & 2, Equipment Group II, Gas Group A, Temperature Class T3, Ambient temp-20°C to +50°C)
	Dust	Ex ibD 22 IP6x T90oC (Approved for Zone 22, Equipment Group II)

SPECIFICATIONS

PHYSICAL

Dimensions (mm)	135 x 55 x 38
Weight (typ) g	400
Battery	725 mAh, 7,2V 12 hrs, typ, 5/5/90 duty cycle

RF SPECIFICATIONS

Frequency Bands (MHz)	380 - 430 806 - 870
Switching Bandwidth TMO (MHz)	50 (380-430) 19 (TX: 806-825, RX:851-870)
Switching Bandwidth DMO (MHz)	50 (380-430) 19 (851-870)
RF Channel Bandwidth (kHz)	25
Transmitter RF Power	1W
RF Power Control	3 Steps of 5 dB
RF Power Level Accuracy	+/- 2 dB
Receiver Class	A & B
Receiver Static Sensitivity (dBm)	-112 minimum, -115 typical
Receiver Dynamic Sensitivity (dBm)	-103 minimum, -107 typical

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature (°C)	-20°C to +50°C (Hazardous Environments) -20°C to +60°C (Non-Hazardous Environments)
Storage Temperature (°C)	-40°C to +85°C (MIL STD 810 C, D)
Humidity	ETS 300 019-1-7 Class 7.3E
Dust and Water	IP65 per IEC 60529
Shock, drop and vibration	ETS 300 019-1-7 Class 5M3

SECURITY FEATURES

Air Interface Encryption	Algorithms TEA1, TEA2, TEA3 Security Classes Class1 (clear), Class2 (SCK), Class3 (DCK, CCK & GCK*)
Key Provisioning	Secure provisioning tool (key variable loader KVL) Over the Air Re-keying (OTAR) for SCK and Class 3 (CCK & GCK*)
Network Access	Temporary Enable / Disable (Stun) Permanent Enable / Disable (Kill)
Authentication	Infrastructure initiated and made mutual by terminal

PERIPHERALS AND ACCESSORIES

Audio	A wide range of audio accessories is available including ATEX certified speaker mics and headsets.
Power & Charging	Solutions for desk top charging and multi-way chargers
Carrying	A range of carrying solutions is available including carry cases, carry strap and belt clips
Programming	Comprehensive solutions available for radio configuration and encryption key loading via Motorola KVL, including support for the Motorola Integrated Terminals Management solution

GPS SPECIFICATIONS

Simultaneous Satellites	12
Mode of Operation	Autonomous or assisted (A-GPS)
GPS Antenna	Integrated in TETRA antenna
Sensitivity	-152 dBm / -182 dBW
Accuracy	5 meter (50% probable)
Location Protocols	ETSI LIP Motorola LRRP

VOICE SERVICES

Talkgroups	2048 (TMO) & 1024 (DMO)
Phone Book	1000 persons
Scan Lists	40 lists, 20 talkgroups / list
TMO Services	Group Call Late entry Private Call Half / Full Duplex Telephony Full Duplex DGNA up to 2047 groups
DMO Services	Group Call Late entry Private Call Compatibility Gateway & Repeater
Emergency	Smart Emergency DMO / TMO / DMO to TMO Hot Mic Configurable timers Location Send on emergency Target Address Individual or Group Alarm Emergency Status
Other Services	Ambience Listening Transmit Inhibit

DATA SERVICES

Status Messaging	Alias Messages 100
Short Data	Inbox 20 messages
Service (SDS)	Target Address Individual or Group Address Voice Interaction Send / receive during calls
Packet Data	Single or Multi Slot 7.2kbps - 28.8 kbps gross
WAP	Integrated Openwave browser WAP 1.2.x and WAP 2.0 compatibility for UDP/IP Stack
PEI	AT Commands TNP1; enables simultaneous SDS & PD

INTERFACES

RS232 PEI	For connection of data devices
Rugged Accessory	For programming and audio accessory connectivity

For more information please contact your local Motorola Authorised Dealer or Distributor



MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their respective owners. © Motorola, Inc. 2009. All rights reserved. Specifications are subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements.

MTP810EX-UK(09/09)

www.motorola.com

Motorola Ltd, Jays Close, Viabes Industrial Estate, Basingstoke, Hampshire, RG22 4PD, UK