



MOTOTRBO R2

PORTABLE TWO-WAY RADIO

A next-level workhorse, the MOTOTRBO™ R2 marries durability and ergonomics to ensure confident, easy handling. And with superior range, configurable audio and seamless integration, the R2 is a reliable addition to an uninterrupted workday.



KEY FEATURES

- VHF, 350MHz, UHF
- 64 channels
- Single-site conventional
- Extended range direct mode
- Dual-capacity direct mode
- Transmit Interrupt
- Dual priority scan
- Quick Call II / MDC1200 Capable
- Secure Enhanced Linux operating system
- Enhanced privacy
- Radio disable/enable
- Remote monitor
- Voice announcement
- Loudness up to 101 phons
- SINC noise suppression
- Acoustic feedback suppression
- Selectable audio profiles
- Received audio leveling
- Sleek & ergonomic form factor
- Rugged to MIL-STD 810
- IP55 (dust and water ingress protection)
- 2 programmable buttons
- Home channel reminder
- Rental timer

SPECIFICATIONS

GENERAL SPECIFICATIONS

Frequency	136-174 MHz	350-400 MHz	400-480 MHz	450-527 MHz
Typical RF output High power	5W	4W	4W	4W
Low power	1W	1W	1W	1W
Channel spacing	12.5/20.0/25.0 kHz	12.5/25.0 kHz	12.5/20.0/25.0 kHz	
Channel capacity				64
Dimension ¹ (H x W x D) with battery				
PMNN4598 high capacity battery			125 x 55 x 37 mm	
PMNN4600 slim battery			125 x 55 x 32 mm	
Weight ² with battery				
PMNN4598 high capacity battery			286 g	
PMNN4600 slim battery			261 g	
Battery life ³ (analog / digital)				
PMNN4598 high capacity battery			19.5 hours / 26.5 hours	
PMNN4600 slim battery			17 hours / 22.5 hours	
Power supply	7.5V (nominal)			
FCC description	AZ489FT3852	n/a	AZ489FT4971	n/a
IC description	109U-89FT3852	n/a	109U-89FT4971	n/a

¹Dimensions at grip area

²Excludes antenna

³Typical battery life, 5/5/90 profile at maximum transmitter power. Actual observed runtimes may vary.



TRANSMITTER SPECIFICATIONS

4FSK digital modulation	12.5 kHz Data: 7K60F1D and 7K60FXD 12.5 kHz Voice: 7K60F1E and 7K60FXE Combination: 7K60F1W
Digital protocol	ETSI TS 102 361-1, -2, -3 DMR Tier II
Conducted/radiated spurious emissions (TIA603E)	< -36 dBm for < 1 GHz ; < -30 dBm for > 1 GHz
Adjacent channel power	> 60 dB @ 12.5 kHz / >70 dB @ 20/25 kHz
Frequency stability	± 0.5 ppm
Modulation limiting	± 2.5 kHz @ 12.5 kHz / ± 4.0 kHz @ 20 kHz / ± 5.0 kHz @ 25 kHz

RECEIVER SPECIFICATIONS

Analog sensitivity (12dB SINAD)	0.18 µV (typical)
Digital sensitivity (5% BER)	0.16 µV (typical)
Conducted/radiated spurious emissions (TIA603E)	< -57 dBm
Intermodulation (TIA603D)	> 70 dB
Adjacent channel selectivity (TIA603D)-1T	> 70 dB @ 20/25 kHz
Adjacent channel selectivity (TIA603E)-2T	> 70 dB @ 20/25 kHz
Spurious rejection TIA603E	> 70 dB
Frequency stability	± 0.5 ppm

AUDIO SPECIFICATIONS

Digital vocoder type	AMBE+2
Audio response	TIA603E
Audio output audio (Rated/Max)	1 W / 3 W
Audio distortion at rated power	3% (typical)
Maximum speech loudness (ISO 532B)	101 phon
Hum and noise	-40 dB @ 12.5kHz / -45 dB @ 20/25 kHz

ENVIRONMENTAL SPECIFICATIONS

Operating temperature ¹	-30°C to 60°C
Storage temperature ¹	-40°C to 85°C
Thermal shock	Per MIL-STD 810C, D, E, F, G, H
Humidity	Per MIL-STD 810C, D, E, F, G, H
Electrostatic discharge	IEC 61000-4-2 Level 4
Dust and water intrusion	IEC60529 IP55
Salt fog	Per MIL-STD 810C/D/E/F/G/H
Packaging test	Per MIL-STD 810C/D/E/F/G/H

MILITARY STANDARDS (MIL-STD 810)

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G		MIL-STD 810H	
	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.6	II	500.6	II
High Temp	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.6	I/A1, II/A1	501.7	I/A1, II/A1
Low Temp	502.1	I	502.2	I, II	502.3	I, II	502.4	I, II	502.6	I, II	502.7	I, II
Temp Shock	503.1	I	503.2	A1/C3	503.3	A1/C3	503.4	I	503.6	I-C	503.7	I-C
Solar Radiation	505.1	II	505.2	I/A1	505.3	I/A1	505.4	I/A1	505.6	I/A1	505.7	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.6	I, III	506.6	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	-	507.6	II/Aggravated	507.6	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-	509.6	-	509.7	-
Blowing Dust & Sand	510.1	I / -	510.2	I, II	510.3	I, II	510.4	I, II	510.6	I, II	510.7	I, II
Vibration	514.2	VIII/CatF, XI	514.3	I/Cat10, II/Cat3	514.4	I/Cat10, III/Cat3	514.5	I/Cat24, II/Cat5	514.7	I/Cat24, II/Cat5	514.8	I/Cat24, II/Cat5
Shock	516.2	I, II	516.3	I, IV	516.4	I, IV	516.5	I, IV	516.7	I, IV	516.8	I, IV ¹

¹Temperatures listed are for radio specifications.

FEATURES

GENERAL

Analog and digital	•
DMR standards compliant ¹	•
64 channels	•
2 programmable buttons	•
Canned text messaging ¹	•
Voice announcements	•
Home channel reminder	•
Late entry ¹	•
Dual priority scan	•
Nuisance Channel Delete	•
Secure Enhanced Linux Operating System	•
TLS-PSK CPS/RM - Radio/Repeater Authentication	•
Rental timer	•
Internal Voice Operated Transmission (VOX)	•
Wide range of accessories	•
IP55 dust and water ingress protection	•
Rugged to MIL-STD 810	•

AUDIO

Acoustic feedback suppressor ¹	•
User-selectable audio profile	•
Trill enhancement for rolling rs	•
SINC noise suppression	◦
Automatic Gain Control	•
Received Audio Leveling	•

SAFETY

Lone worker ¹	•
Digital emergency ¹	•
Emergency search tone ¹	•
Basic privacy ¹	•
Enhanced privacy ¹	◦
Transmit interrupt ¹	•
Remote monitor ²	•
Radio disable / enable ²	•

SYSTEMS

Dual Capacity Direct Mode ¹	•
Single-site conventional	•
Extended Range Direct Mode ¹	•
IP Site Connect ¹	•
Capacity Plus Single Site, Two Repeaters ¹	◦

ANALOG FEATURES

Lone worker	•
Emergency alert	•
Analog scrambling	•
Quick Call II / MDC1200 Capable	•

- Feature is standard
- Feature is optional

¹ Digital feature

² Decode

For more information, please visit
motorolasolutions.com/R2



Motorola Solutions, Inc. 500 West Monroe Street, Chicago, IL 60661 U.S.A. motorolasolutions.com

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2023 Motorola Solutions, Inc. All rights reserved. 10-2023 [CK05]

MOTOTRBO
R2