



UNCOMPROMISING QUALITY. UNBEATABLE SIZE.

APX™ 2000 PROJECT 25 PORTABLE RADIO

Your people work in the toughest conditions, in some of the noisiest places – at mines, near manufacturing machinery, or in the middle of a bushfire. Communicating with them clearly is imperative for their safety.

They need a radio that is exceptionally durable, overcomes external noise and outlasts the longest shifts. The APX 2000 radio combines the feature-rich technology first responders and industrial users rely on with the real-world affordability they require.

The APX 2000 is big on the attributes you expect from APX in the smallest P25 Phase 2 portable in the industry. Flexible and versatile, it's easy to use, extremely durable, with advanced features for improved safety and exceptional noise suppression for clear communications, so you can interoperate with other teams and P25 systems the moment you need to.

APX PERFORMANCE, INSIDE AND OUT

The APX 2000 leverages the industry-leading hallmarks of the APX family of P25 TDMA portables. Starting with an innovative two-microphone design that produces outstanding voice quality and suppresses background noise so users can speak and hear clearly above diesel engines, sirens and heavy equipment.

Simplified controls and an enlarged multifunction knob are easy to turn on or off, set volume and switch talk groups, even while wearing gloves. High-spec radio frequency performance ensures excellent coverage in challenging environments.

FIRST TO WORK, LAST TO LEAVE

Reporting from the field or a power line, the compact APX 2000 stands up to challenging conditions. It's IP67 and MIL-STD certified to withstand dust, heat, drops and water immersion, with a tempered glass display that resists scratches, abrasions and chemical solvents.

Loaded with advanced P25 features – including mission critical wireless Bluetooth® – that increase communication flexibility, GPS for quickly locating personnel and assets, and additional language support for international users – the APX 2000 improves safety, from the moment it's powered on until the last person heads home.

AFFORDABILITY MEETS PORTABILITY

The APX 2000 is P25 Phase 2 capable for twice the voice capacity, so you can add more users without adding more frequencies or infrastructure. Backwards and forwards compatible with all Motorola mission critical radio systems, the APX 2000 portable keeps communications running without running up costs.

ACCESSORIES AS POWERFUL AS APX 2000

- Complete portfolio of remote speaker microphones, headsets and mission critical wireless Bluetooth® accessories.
- Designed, tested and certified for optimum performance with your radio.
- High-powered IMPRES™ batteries that have a slim design to fit the compact radio size.



FEATURES AND BENEFITS:

Available in 700/800 MHz, VHF, UHF R1, and UHF R2 bands

Trunking standards supported:

- ASTRO®25 digital trunked operation
- SmartZone®, SmartZone Omnilink, SmartNet®

Conventional system:

- Analogue MDC-1200 and Digital APCO P25

Narrow and wide bandwidth digital receiver
(6.25 kHz equivalent / 12.5 kHz / 25 kHz)

Embedded digital signaling (ASTRO & ASTRO 25)

Available in two models

Integrated GPS capable

Lightbar with Intelligent Lighting

Radio Profiles

Unified Call List

User programmable Voice Announcement

International Language Support: Spanish, French, Portuguese,
Russian, and Traditional Chinese

Meets Applicable MIL-STD-810C, D, E, F and G

IP67 standard
(submersible 1 metre, 30 minutes)¹

Superior Audio Features:

- 0.5 W high audio speaker
- 2-mic noise canceling technology

Utilises Windows XP, Vista and Windows 7 Customer
Programming Software (CPS)

- Supports USB communications
- Built in FLASHport™ support

Full portfolio of accessories including IMPRES batteries,
chargers and audio devices²

OPTIONAL FEATURES:

Mission Critical Wireless

Programming Over Project 25

Text Messaging

¹ Radios meet industry standards (IPx7) for immersion.

² Chargers and batteries for the APX 2000 radios do not interoperate with other APX radios

TRANSMITTER - TYPICAL PERFORMANCE SPECIFICATIONS

	700/800	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	700 MHz 800 MHz	763-776, 793-806 MHz 806-825, 851-870 MHz	136-174 MHz	380-470 MHz 450-520 MHz
Channel Spacing		25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz
Maximum Frequency Separation		Full Bandsplit	Full Bandsplit	Full Bandsplit
Rated RF Output Power Adj ¹		1-3 Watts Max	1-5 Watts Max	1-5 Watts Max
Frequency Stability ¹ (-30°C to +60°C; +25°C Ref.)		±0.00010 %	±0.00010 %	±0.00010 %
Modulation Limiting ¹		±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz
Emissions (Conducted and Radiated) ¹		-75 dB	-75 dB	-75 dB
Audio Response ¹		+1, -3 dB	+1, -3 dB	+1, -3 dB
FM Hum & Noise	25 kHz 12.5 kHz	-47 dB -45 dB	-47 dB -47 dB	-47 dB -45 dB
Audio Distortion ¹	25 kHz 12.5 kHz	1.00%	1.00%	1.00%

BATTERIES FOR APX 2000

Battery Capacity / Type	Dimensions (HxWxD)	Weight	Battery Part Number	Battery Capacity
Li-Ion IMPRES 1900 mAh IP67	114.5x55.04x17.85	150 grams	NNTN8128A	1900 mAh
Li-Ion IMPRES 2300 mAh IP67 Non-FM	114.5x55.04x23.15	160 grams	PMNN4424AR	2300 mAh
Li-Ion IMPRES 2300 mAh IP67 FM	114.5x55.04x23.15	160 grams	NNTN8129A	2300 mAh



RADIO MODELS		
	MODEL 2	MODEL 3
Display	Full bitmap colour LCD display 3 lines of text x 14 characters 1 line of icons 1 menu line x 3 menus White backlight	Full bitmap colour LCD display 3 lines of text x 14 characters 1 line of icons 1 menu line x 3 menus White backlight
Keypad	Backlight keypad 3 soft keys 4 direction Navigation key Home and Data buttons	Backlight keypad 3 soft keys 4 direction navigation key 4x3 keypad Home and Data buttons
Channel Capacity	512	512
FLASHport Memory	64 MB	64 MB
700/800 MHz (763-870 MHz)	H52UCF9PW6AN	H52UCH9PW7AN
VHF (136-174 MHz)	H52KDF9PW6AN	H52KDH9PW7AN
UHF Range 1 (380-470 MHz)	H52QDF9PW6AN	H52QDH9PW7AN
UHF Range 2 (450-520 MHz)	H52SDF9PW6AN	H52SDH9PW7AN
Buttons & Switches	Large PTT button ■ Multi-function knob ■ Orange emergency button ■ 3 programmable side buttons	

TRANSMITTER CERTIFICATION	
700/800 (764-869 MHz)	AZ489FT7050 (Basic)/AZ489FT7049 (Expanded)
VHF (136-174 MHz)	AZ489FT3825 (Basic)/AZ489FT3828 (Expanded)
UHF Range 1 (380-470 MHz)	AZ489FT4907 (Basic)/AZ489FT4905 (Expanded)
UHF Range 2 (450-520 MHz)	AZ489FT4909 (Basic)/AZ489FT4910 (Expanded)

FCC EMISSIONS DESIGNATORS	
FCC Emissions Designators	11K0F3E, 16K0F3E, 8K10F1D, 8K10F1E, 8K10F1W, 20K0F1E

POWER SUPPLY	
Power Supply	One rechargeable Li-Ion 1900 mAh battery standard, or 2300 mAh high cap Li-Ion.

RECEIVER - TYPICAL PERFORMANCE SPECIFICATIONS					
		700/800	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	700 MHz 800 MHz	763-776 MHz 851-870 MHz	136-174 MHz	380-470 MHz	450-520 MHz
Channel Spacing		25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz
Maximum Frequency Separation		Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Audio Output Power at Rated ¹		500mW	500mW	500mW	500mW
Frequency Stability ¹ (-30°C to +60°C; +25°C Ref.)		±0.00010 %	±0.00010 %	±0.00010 %	±0.00010 %
Analog Sensitivity ³	12 dB SINAD	0.266µV	0.216µV	0.234µV	0.234µV
Digital Sensitivity ⁴	1% BER (800 MHz) 5% BER	0.400µV 0.266µV	0.277µV 0.188µV	0.307µV 0.207µV	0.307µV 0.207µV
Selectivity ¹	25 kHz channel 12.5 kHz channel	76 dB 67 dB	76 dB 70 dB	76 dB 67 dB	76 dB 67 dB
Intermodulation		75 dB	76 dB	77 dB	77 dB
Spurious Rejection		76.6 dB	85 dB	80.3 dB	90 dB
FM Hum and Noise	25 kHz 12.5 kHz	-53 dB -47 dB	-51 dB -45 dB	-50 dB -45 dB	-50 dB -45 dB
Audio Distortion ¹		1.00%	1.00%	1.00%	1.00%

BASIC SOFTWARE PACKAGE

3600 or 9600 Trunking
Conventional
Advanced Digital Privacy (ADP).

EXPANDED SOFTWARE PACKAGE

3600 or 9600 Trunking
Conventional
Advanced Digital Privacy (ADP)
870 Channel Capacity
Integrated Voice & Data (IV&D)
POP25 (Over the air programming)
GPS Activation
Mission Critical Wireless (Bluetooth) Activation
Man Down Functionality.

CUSTOMISED SOFTWARE PACKAGES

Contact your account manager to discuss available options.

PORTABLE MILITARY STANDARDS 810 C, D, E, F & G										
	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Basic Hot	501.5	I/A1, II/A2
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1
Temperature Shock	503.1	I	503.2	I/A1C3	503.3	I/A1C3	503.4	I	503.5	I/C
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	1 Proc	507.5	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	1 Proc	509.5	1 Proc
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I
Blowing Sand	1 Proc	1 Proc	510.2	II	510.3	II	510.4	II	510.5	II
Vibration	514.2	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	I/24	514.6	I/24
Shock	516.2	I, III, V	516.3	I, V, VI	516.4	I, V, VI	516.5	I, V, VI	516.6	I, V, VI
Shock (Drop)	516.2	II	516.2	IV	516.4	IV	516.5	IV	516.6	IV

GPS SPECIFICATIONS	
Channels	12
Tracking Sensitivity	-159 dBm
Accuracy ⁵	<10 metres (95%)
Cold Start	<60 seconds (95%)
Hot Start	<10 seconds (95%)
Mode of Operation	Autonomous (Non-Assisted) GPS

ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature ⁶	-30°C / +60°C
Storage Temperature ⁶	-40°C / +85°C
Humidity	Per MIL-STD
ESD	IEC 801-2 KV
Water and Dust Intrusion	IP67
Housing Availability	Black only

DIMENSIONS OF THE RADIOS WITHOUT BATTERY		
	Inches	Millimetres
Length	5.26	133
Width at Push-To-Talk button	2.37	60.2
Depth at Push-To-Talk button	1.72	43.6
Width Top	2.56	65
Depth Top	2.13	43
Weight of the radios without battery	9.17 oz	260 g

¹ Measured in the analogue mode per TIA / EIA 603 under nominal conditions

² When used with an FM approved intrinsically safe radio

³ Measured conductively in analogue mode per TIA / EIA 603 under nominal conditions.

⁴ Measured conductively in digital mode per TIA / EIA IS 102.CAAA under nominal conditions.

⁵ Accuracy specs are for long-term tracking (95th percentile values >5 satellites visible at a nominal -130 dBm signal strength).

⁶ Temperatures listed are for radio specifications. Battery storage is recommended at 25°C, ±5°C to ensure best performance.

Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements.

For more information on how to make your business more efficient and better connected, visit www.motorolasolutions.com.au

www.motorolasolutions.com.au

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2012 Motorola Solutions, Inc. All rights reserved.

BTB/MA751-APX2000 - 09/15

