

VXR-1000 Series

VHF/UHF Cross-band Mobile Repeater

SPECIFICATION SHEET

Dependable, Expanded Portable Coverage

The VXR-1000 is a cost-effective addition to a mobile fleet that provides portable radios extended range in low-coverage areas using the high output power of mobile radios. Get dependable coverage throughout your system without the costly addition of site equipment.

Compact Size for Easy Installation

Fits easily on top of a mobile radio or anywhere in the vehicle (trunk, sidewall, etc.) without taking up space.

Easily Integrate with Existing Systems

The VXR-1000 will interface with most brands of mobile radios and works with most Low Band, VHF and UHF systems. It can also be programmed to work with most trunking protocols.

First-On-Scene Logic for Reliability

If multiple vehicles are at one location, the VXR-1000 will adjust to recognize one master repeater in operation at a time to ensure communications is never disrupted.

Bypass The Main System

When direct, secure communications is needed to a portable radio user, the VXR-1000 can talk directly to the portable radio and avoid communications being transmitted through the repeater system.

Secure Mobile Communications

The VXR-1000 includes Voice Inversion Encryption that provides the connected mobile radio device with secure communications capability.


Exclusive Auto-Range Transpond System – ARTS™

Only Vertex Standard radios are designed to inform you when you and another ARTS[™]-equipped station are within communication range. If out of range for more than 2 minutes, your radio senses no signal has been received and beeps to alert you. The base station can then alert the field unit to move back in range. A great solution to keep your workers coordinated.



The Vertex Standard Difference

Our number one goal is achieving superior customer satisfaction by delivering products and services that exceed your expectations. Vertex Standard radios are built to last and are backed by an industryleading 3 year warranty – another great reason to choose Vertex Standard. Ask your Dealer for more details.





VXR-1000 Series

SPECIFICATION SHEET

Additional Features

- 16 Channel capacity
- CTCSS / DCS Encode and Decode
- D-sub 9-pin connector
- Local volume control (with external speaker)

Accessories

- MH-67A8J: Standard microphone
- MLS-100: External speaker, 12W

VXR-1000 Series Specifications

	VHF	UHF				
General Specification						
Frequency Range	150 – 174 MHz	450 – 470 MHz				
Number of Channels	16					
Power Supply Voltage	13.8V DC					
Channel Spacing	12.5 / 25 kHz	12.5 / 25 kHz				
Operating Temperature Range	-22° F to +140° F (-30° C to +60° C)					
Frequency Stability	±2.5 ppm					
RF Input-Output Impedance	50 Ohms					
Dimension (W \times H \times D)	4.4 x 1.0 x 5.4 inches (111 x 25.4 x 136 mm)					
Weight (Approx.)	14.1 oz (400 g)					
Receiver Specification: measured by TIA/EIA-603						
Sensitivity 12dB SINAD	0.30 µV	0.35 µV				
Intermodulation	60 0	60 dB				
Spurious and Image Rejection	60 c	60 dB				
Audio Output	I W @ 8 Ohms					
Transmitter Specification: measured by TIA/EIA-603						
Output Power	5/2.5/1/0.5 W					
Modulation	16K0F3E, 11K0F3E					
Maximum Deviation	±5.0 kHz / ±2.5 kHz					
Audio Distortion	< 5% @ 1 kHz					
Conducted Spurious Emission	60 dB belov	w carrier				

Applicable MIL-STD

Standard	MIL 810C Methods/ Procedures	MIL 810D Methods/ Procedures	MIL 810E Methods/ Procedures
Dust	510.1/Procedure 1	510.2/Procedure I	510.3/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure 1	514.4/Procedure 1
Shock	516.2/Procedure I,II,III,V	516.3/Procedure I,III,IV,V,VI	516.4/Procedure I,III,IV,V,VI

Specifications are subject to change without notice or obligation. VERTEX STANDARD is अ站 細心 (おんんかいのなんの) なおお応て 道敏 8逆All other product or service names are the property of their respective owners. © Vertex Standard Co. Ltd. 2013 (明道都 の ふっしょうな)

NSS1000_F€®D€FGŠY

vertexstandard.com/lmr